

PART NO.	SIZE	LOAD RANGE	TREAD DEPTH 1/32 INCH	OVERALL DIAMETER INCH	OVERALL WIDTH INCH	MAX. LOAD SINGLE	MAX.PRESS. SINGLE	APPROVED RIM WITH RANGE INCH
285-7516AMP/CA2	285/75R16	E	15	32.8	11.2	3,750 lbs.	80 psi	7.5 - 9"
305-7016AMP/CA2	305/70R16	E	15	32.8	12.2	3,525 lbs.	65 psi	8 - 9.5"
285-7017AMP/CA2	285/70R17	E	15	32.7	11.5	3,195 lbs.	80 psi	7.5 - 9"
305-6517AMP/CA2	305/65R17	E	15	32.6	12.2	3,195 lbs.	65 psi	8.5 - 11"
315-7017AMP/CA2	315/70R17	E	15	34.4	12.7	3,195 lbs.	65 psi	8 - 11"
285-6518AMP/CA2	285/65R18	E	15	32.5	11.5	3,640 lbs.	80 psi	8 - 10"
325-6518AMP/CA2	325/65R18	E	15	34.6	13.0	3,860 lbs.	65 psi	9 - 12"
275-6020AMP/CA2	275/60R20	E	15	32.9	10.9	3,415 lbs.	80 psi	7.5 - 9.5"
285-5520AMP/CA2	285/55R20	E	15	32.3	11.6	3,305 lbs.	80 psi	8 - 10"
305-5520AMP/CA2	305/55R20	E	15	33.2	12.4	3,195 lbs.	65 psi	8.5 - 11"
325-6020AMP/CA2	325/60R20	E	15	35.3	13.0	3,750 lbs.	65 psi	9 - 12"